RL-H5A



Standard Kit



- RL-H5A Unit
- Battery Holder DB-79A
- Battery Adapter(DC/DC converter) DD-79
- Power cable PC-28
- Carrying Case
- User Manual
- Safety Notice/Standard Kit List

SPECIFICATIONS

RL-H5A			
Operating range		Diameter Approx. 2 to 800 m (When using LS-80L)	
Accuracy		±10"	
Self-leveling range:		±5°	
Manual slope settable range		±5° (When the instrument is installed on the 0° surface)	
Laser source:		Laser diode (Visible, 635 nm) CDRH (FDA) Class Illa, IEC Class 3R	
Rotational speeds		600 r.p.m	
Status alerts		Hi and low battery	
Dust and water resistance		IP66 (IEC60529: 2001)	
Operating temperature		-20 to 50°C (-4 to 122°F)	
Size		172(W) x 211(D) x 205(H) mm	
Weight	Dry battery type	2.3 kg (5.1 lbs) (with dry cell batteries)	
	External power supply type	1.8 kg (4.0 lbs) (with DD-79)	
Power source/Operating time at 20°C (68°F)		4xD size dry cell batteries (alkaline) /100 hours	

DD-79 (DC/DC Convertor)

Input voltage	12V,24V DC
Output voltage	DC 6V/1.5A MAX 9W
Opereting temperature	-20 to 50°C (-4 to 122°F)
Size	120(W) x 150(D) x 48(H) mm
Weight	250g

PC-28 (Power Cable)

Input voltage	DC12 to 24V
Withstand current	5A
Opereting temperature	-20 to 50°C
Terminal figure	Clip type
Cable length	Approx. 5m

TOPCON

TOPCON CORPORATION

75-1 Hasunuma-cho, Itabashi-ku, Tokyo 174-8580, Japan

www.topcon.co.jp

<Contact to>

Topcon Sokkia India Private Limited

Unit No.101 to 106A, 1st Floor, ABW Tower, MG Road, Sector-25, IFFCO Chowk, Gurgaon, Haryana-122001.India Phone: 91-124-484-7676
Email : sales@topconsokkia.ind.in
Web : http://www.topconsokkia.ind.in/

©2018 Topcon Corporation All rights reserved. P-233-1 TSI

- Specifications may vary by region and are subject to change without notice. - Other trademarks and trade names are those of their respective owners

Your local Authorized Dealer is:

RL-H5A



RL-H5A

Rotating Laser





Smart & Tough! All Round Rotating Laser

- + 10 Arc second (1.5mm@30m) horizontal accuracy
- Long range operation 800m
- External power supply system
- Manual slope capability
- Safety lock and tough IP66 rating
- High quality TOPCON laser
- User friendly design

Reliable partner with 3 "Highs"!

RL-H5A

High accuracy

High reliability

High quality

User Friendly Design

Big handle, easy to grab even with glove on. Clear operational button, easy to understand what to do. New design to care for the user's operation-

High quality of external power supply system

Battery Adapter (DC/DC convertor) DD-79

- Input voltage DC12V DC24V(especially for car battery)
- Connector for high environment performance

Power Cable PC-28

- Connector for high environment performance
- 5m length for installation at high place
- Push-Pull lock structure for easy one-handed insertion and removal
- Alligator clip for car battery





High Accuracy for large area

From Construction to Agriculture

+ 10 Arc second (1.5mm@30m) high horizontal accuracy. Large range operation 800m.
All round rotating laser for pile foundation for buildings, leveling work for large construction site or farmland.



Reliable leveling work



Reliable even at the vibrated environment

Electronic self-leveling mechanism inside makes stable laser beam even at vibrated environment where pendulum cannot perform well. Also, safety lock (high alert) function let the operator know in the case that the unit get slanted and its height changes. You can rely on it to use.



Tough IP66 Rating

With the IP66 rating, RL-H5A is "Construction Site Tough" and can withstand dust, a sudden shower and even torrential rainfall.

High Quality Topcon Laser

Topcon believes the product on site must have reliability from the customer.

Therefore, the tough environmental test, simulated as tough construction site, is performed for RL-H5A.



High/Low Temperature Test



Repeatability Accuracy Test



bration Test



Laser Endurance Test



Drop Test



Rotating Head Endurance Test